

View Online at <https://aerobasegroup.com/nsn/5930-01-536-9933>

**Thread Class:**

2a single threaded stud

**Overall Height:**

Between 0.590 inches and 0.604 inches

**Body Height:**

0.437 inches

**Overall Diameter:**

0.640 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32 single threaded stud

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.138 inches single threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

110.00 actuation point degrees fahrenheit and 90.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Product Name:**

Thermostatic switch

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Thread Series Designator:**

Unc single threaded stud

**Specification Data:**

81349 - mil-prf-24236/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0

**Mil-std (military Standard):**

Mil-prf-24236 spec.