NSN 5930-01-538-9320



Thermostatic Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-538-9320 **Overall Length:** Between 1.160 inches and 1.260 inches **Overall Height:** Between 0.260 inches and 0.325 inches **Body Diameter:** 0.640 inches **Body Height:** 0.500 inches **End Application:** An/sqq-8 (v) 15 unit 804, system equipment rack **Tempurature Sensing Element Type:** Internal sensor **Mounting Method: Bracket Contact Action Stimulus:** Decrease **Nonpile-up Contact Arrangement:** 1 pole, single throw, both positions maintained **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage **Contact Adjustability:** Actuation point not adjustable **Contact Stimulus Rating:** 120.00 actuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage **Product Name:** Switch, thermostatic (bimetallic) Frequency In Hertz: 60.0 first voltage Media For Which Designed: Gas or solid **Style Designator:** Disc w/flange

Specification Data: 81349 - mil-prf-24236/1 government specification Shelf Life: N/a

Unit Of Measure:

NSN 5930-01-538-9320

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0

Mil-std (military Standard):

Mil-prf-24236 spec.