# NSN 5930-01-543-1203

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-543-1203

## Thread Class:

2a single mounting facility

## **Overall Length:**

3.520 inches

## **Overall Height:**

1.740 inches

## **Overall Width:**

2.500 inches

## Individual Section Quantity:

1

### Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

### Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

#### End Application:

**REMO-TE-CON-TROL** 

### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

### Features Provided:

Actuator knob and legend plate

### Thready Qty Per Inch (tpi):

32 single mounting facility

### Thread Size:

0.164 inches single mounting facility

### **Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

### Mounting Facility Pattern:

Four position rectangular single mounting facility

### Switch Actuator Indexing Position Quantity:

2 single actuator

#### **Terminal Type:**

Tab w/screw

### **Contact Load Current Rating:**

750.0 milliamperes inductive load highest ac voltage rating at sea level

### **Product Name:**

Switch, selector, flush mounting, 2pos., element 3d

#### **Special Features:**

Two positions: run and emer run

### Style Designator:

Tap, circuit selector

# NSN 5930-01-543-1203

Rotary Switch - Page 2 of 2



Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

