NSN 5930-01-543-1206

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-543-1206

Thread Class:

2a single mounting facility

Overall Length:

3.520 inches

Overall Height:

1.740 inches

Overall Width:

2.500 inches

Individual Section Quantity:

.

Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

End Application:

Hand held remote controller 24048-012

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Load Current Rating:

750.0 milliamperes inductive load highest ac voltage rating at sea level

Product Name:

Switch, selector, flush mounting, 2pos., element 2e

Special Features:

Two positions: cw and ccw

Style Designator:

Tap, circuit selector

NSN 5930-01-543-1206

Rotary Switch - Page 2 of 2



Ī	hread	Series	Desig	nator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0