

View Online at <https://aerobasegroup.com/nsn/5930-01-543-1208>

**Thread Class:**

2a single mounting facility

**Overall Length:**

3.520 inches

**Overall Height:**

1.740 inches

**Overall Width:**

2.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.620 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.250 inches single mounting facility

**End Application:**

Hand held remote controller 24048-012

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

750.0 milliamperes inductive load highest ac voltage rating at sea level

**Product Name:**

Switch, selector, flush mounting, 3pos., element 6d

**Special Features:**

Three positions: off, slow and fast

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0