## NSN 5930-01-543-1208

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-543-1208

**Thread Class:** 

2a single mounting facility

**Overall Length:** 

3.520 inches

**Overall Height:** 

1.740 inches

**Overall Width:** 

2.500 inches

**Individual Section Quantity:** 

1

**Longest Horizontal Distance Between Mounting Centers:** 

1.620 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

1.250 inches single mounting facility

**End Application:** 

Hand held remote controller 24048-012

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:** 

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:** 

440.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Terminal Type:** 

Tab w/screw

**Contact Load Current Rating:** 

750.0 milliamperes inductive load highest ac voltage rating at sea level

**Product Name:** 

Switch, selector, flush mounting, 3pos., element 6d

**Special Features:** 

Three positions: off, slow and fast

Style Designator:

Tap, circuit selector

## NSN 5930-01-543-1208

Rotary Switch - Page 2 of 2



	T	hr	ead	<b>Series</b>	Design	nator
--	---	----	-----	---------------	--------	-------

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0