NSN 5930-01-545-6750

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-545-6750

| Overall Length: |
|--|
| 7.200 inches |
| Overall Height: |
| 1.270 inches |
| Overall Width: |
| 6.000 inches |
| Body Length: |
| 5.270 inches |
| End Application: |
| Light amphbious resupply craft (larc v) slep |
| Operating Tempurature Rating: |
| Between -20.0 degrees fahrenheit and 240.0 degrees fahrenheit |
| Mounting Method: |
| Input port and outlet connection and bracket |
| Contact Action Stimulus: |
| Increase |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained |
| Terminal Type: |
| Wire lead |
| Contact Load Current Rating: |
| 10.0 amperes resistive load first voltage |
| Contact Adjustability: |
| Actuation point adjustable, preset |
| Contact Adjustment Range: |
| +2.00/+20.00 actuation point gallons per minute |
| Contact Adjustment Type: |
| Internal actuation point pointer with scale |
| Contact Stimulus Rating: |
| 2.00 actuation point gallons per minute and 20.00 deactuation point gallons per minute |
| Contact Voltage Rating In Volts: |
| 250.0 ac at sea level first voltage |
| Product Name: |
| Flow switch |
| Special Features: |
| Port size: 3/4 inch (sae 12) |
| Media For Which Designed: |
| Liquid or gas |
| Style Designator: |
| Rectangular |
| Shelf Life: |
| N/a |

NSN 5930-01-545-6750

Flow Switch - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A048b0