

View Online at <https://aerobasegroup.com/nsn/5930-01-546-3173>

Thread Class:

2b single pressure connection

Thread Length:

0.500 inches single pressure connection

Overall Length:

5.750 inches

Outside Diameter:

0.438 inches single connection

Overall Height:

10.813 inches

Overall Width:

3.000 inches

Body Height:

2.750 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Shortest Horizontal Distance Between Mounting Centers:

1.500 inches

Longest Vertical Distance Between Mounting Centers:

4.250 inches

End Application:

Seawolf class ssn

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

5000.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+500.00/+5000.00 actuation point pounds per square inch and +350.00/+4610.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Pressure Connector Type:

Inverted flare, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0