

View Online at <https://aerobasegroup.com/nsn/5930-01-550-4323>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and moisture proof

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Illuminated Actuator Color:**

Blue single actuator

**Actuator Inscription:**

10jg and sel single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Situational awareness bridge display system

**Mounting Surface To Terminal End Distance:**

1.742 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Product Name:**

Pushbutton switch

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc

**Special Features:**

Inscription number: 35678 (10jg) (sel); led illuminated; 4-solderless quik connect; 5-spdt-sb gold; a-dripproof w/heavy impact shock; 4-alternate, single, 1 xommon; b-splitlegend; w-28 volt

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

4 quick disconnect, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0