## NSN 5930-01-550-4333



Push Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-01-550-4333 **Body Style:** Panel mounted **Hazardous Locations/environmental Protection:** Shock resistant and moisture proof **Body Width:** 0.750 inches **Body Height:** 0.750 inches **Illuminated Actuator Color:** Blue single actuator **Actuator Inscription:** Stkops, call in if single actuator **Maximum Voltage Rating In Volts:** 28.0 dc **End Application:** Situational awareness bridge display system **Mounting Surface To Terminal End Distance:** 1.742 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Product Name:** Pushbutton switch **Contact Load Current Rating At Maximum Rated Voltage:** 4.000 amperes resistive dc **Special Features:** Inscription number: 35681 (stkops) (call in jf); led illuminated; 6-solderless quikconnect; f-4spdt-sb gold; 3-dripproof w/heavy impact shock; 1-momentary, single, 1 common; b-split legend; w-28 volt **Precious Material And Location:** Contacts gold **Terminal Type And Quantity:** 6 quick disconnect, female Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A053a0