

View Online at <https://aerobasegroup.com/nsn/5930-01-555-4557>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

0.860 inches

**Bushing Length:**

0.470 inches

**Body Length:**

1.100 inches

**Body Width:**

0.860 inches

**Body Height:**

1.270 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.660 inches

**Actuator Free Position Height:**

0.660 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Cp-201cs dual workstation

**Mounting Surface To Terminal End Distance:**

1.270 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel and terminal

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit

**Product Name:**

Switch, power opt1

**Contact Load Current Rating At Maximum Rated Voltage:**

16.000 amperes resistive ac

**Special Features:**

Case material: thermoplastic; terminals: copper alloy

**Precious Material And Location:**

Plated contacts silver

**Terminal Type And Quantity:**

8 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0