NSN 5930-01-560-5596

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-560-5596

To Length:

| Body Style: |
|--|
| Hole mounted |
| Center To Center Distance Between Mounting Facilities Parallel |
| 0.260 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.220 inches |
| Body Height: |
| 0.260 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.091 inches |
| Actuator Style: |
| Leaf |
| Maximum Voltage Rating In Volts: |
| 48.0 dc |
| End Application: |
| An/wld- (v) remote mine hunting system |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Switch Release Force: |
| 0.7 ounces |
| Switch Actuating Force: |
| 5.3 ounces |
| Product Name: |
| Micro switch |
| Actuator Movement: |
| 0.051 pretravel inches and 0.008 overtravel inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 0.100 amperes resistive dc |
| Precious Material And Location: |
| Plated contacts gold and contacts silver |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| |

NSN 5930-01-560-5596

Sensitive Switch - Page 2 of 2



Fiig:

A053a0