## NSN 5930-01-560-5596

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-560-5596

To Length:

| Body Style:  |
|--|
| Hole mounted   |
| Center To Center Distance Between Mounting Facilities Parallel |
| 0.260 inches   |
| Body Length:   |
| 0.500 inches   |
| Body Width:  |
| 0.220 inches   |
| Body Height:   |
| 0.260 inches   |
| Unthreaded Mounting Hole Diameter:                             |
| 0.091 inches   |
| Actuator Style:  |
| Leaf   |
| Maximum Voltage Rating In Volts:                               |
| 48.0 dc  |
| End Application:   |
| An/wld- (v) remote mine hunting system                         |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Unthreaded hole  |
| Switch Release Force:  |
| 0.7 ounces   |
| Switch Actuating Force:  |
| 5.3 ounces   |
| Product Name:  |
| Micro switch   |
| Actuator Movement:   |
| 0.051 pretravel inches and 0.008 overtravel inches             |
| Contact Load Current Rating At Maximum Rated Voltage:          |
| 0.100 amperes resistive dc                                     |
| Precious Material And Location:                                |
| Plated contacts gold and contacts silver                       |
| Terminal Type And Quantity:                                    |
| 3 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
|  |

## NSN 5930-01-560-5596

Sensitive Switch - Page 2 of 2



Fiig:

A053a0