NSN 5930-01-566-0928

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-566-0928

Overall Length:
2.000 inches
Overall Height:
1.120 inches
Body Diameter:
1.650 inches
Mounting Slot Width:
0.170 inches
Body Height:
0.790 inches
Distance Between Mounting Facility Centers:
Between 1.560 inches and 1.690 inches
Longest Horizontal Distance Between Mounting Centers:
2.000 inches
Shortest Horizontal Distance Between Mounting Centers:
1.550 inches
End Application:
Major/critical applications
Tempurature Sensing Element Type:
Internal sensor
Mounting Facility Circle Radius:
0.930 inches
Operating Tempurature Rating:
Between 104.0 degrees fahrenheit and 338.0 degrees fahrenheit
Mounting Method:
Plug-in and slot
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 two circuit, both positions maintained
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
25.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
14.00 differential point degrees fahrenheit and 100.00 differential point degrees fahrenheit
Contact Voltage Rating In Volts:
240.0 ac at sea level second voltage

240.0 ac at sea level second voltage

NSN 5930-01-566-0928

Thermostatic Switch - Page 2 of 2



Product Name:

3/4in bimetallic disc thermostat

Special Features:

Additional electrical ratings 120vac, 10fla, 60lra; 240vac, 5fla, 30lra, 100000 cycles; for the following applications-h.V.A.C, commercial food equipment, major appliances, medical/lab equipment

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Supplementary Features:

Automatic reset; contacts open 120+/-9 and contacts close 140+/-5; normally open; contacts close on temperature rise; temperature

sensitive snap action; thermally and electrically insulated; t series

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0