NSN 5930-01-567-2520

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-567-2520

| Body Style: | | | | | | |
|---|--|--|--|--|--|--|
| Bushing mount | | | | | | |
| Hazardous Locations/environmental Protection: | | | | | | |
| Moisture resistant | | | | | | |
| Bushing Length: | | | | | | |
| 0.449 inches | | | | | | |
| Body Length: | | | | | | |
| 1.236 inches | | | | | | |
| Body Width: | | | | | | |
| 1.260 inches | | | | | | |
| Body Height: | | | | | | |
| 0.590 inches | | | | | | |
| Case Material: | | | | | | |
| Plastic | | | | | | |
| Actuator Style: | | | | | | |
| Round | | | | | | |
| Actuator Diameter: | | | | | | |
| 0.236 inches | | | | | | |
| Actuator Height: | | | | | | |
| 0.688 inches | | | | | | |
| Actuator Position-action Relationship: | | | | | | |
| Center position maintained and left position maintained and right position maintained | | | | | | |
| Actuator Color: | | | | | | |
| Black single actuator | | | | | | |
| Maximum Voltage Rating In Volts: | | | | | | |
| 250.0 ac and 28.0 dc | | | | | | |
| End Application: | | | | | | |
| 819698 (53711), capture spine | | | | | | |
| Mounting Surface To Terminal End Distance: | | | | | | |
| 1.236 inches | | | | | | |
| Inclosure Type: | | | | | | |
| Fully enclosed | | | | | | |
| Mounting Method: | | | | | | |
| Panel and terminal and threaded bushing | | | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | | | |
| 15.000 amperes resistive ac and 15.000 amperes resistive dc | | | | | | |
| Precious Material And Location: | | | | | | |
| Contacts silver | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 3 screw | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |

NSN 5930-01-567-2520 Toggle Switch - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

Demilitarization:

No

Fiig:

A053a0