

View Online at <https://aerobasegroup.com/nsn/5930-01-567-7747>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.186 inches and 0.190 inches

Body Length:

0.510 inches

Body Width:

0.210 inches

Body Height:

Between 0.340 inches and 0.360 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.057 inches and 0.067 inches

Actuator Height:

0.055 inches

Actuator Free Position Height:

0.355 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

4.0 ounces

Product Name:

Switch

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.001 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.500 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

This item is an altered item from ms24547-3 nsn 5930-00-525-5562: leads shortened to .030"min, .050"max and modified leads solder coat with sn63bs per 00-s-571

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0