

View Online at <https://aerobasegroup.com/nsn/5930-01-584-7270>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.380 inches

**Body Length:**

0.780 inches

**Body Width:**

0.250 inches

**Body Height:**

0.400 inches

**Unthreaded Mounting Hole Diameter:**

0.090 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.400 inches

**Actuator Length:**

0.860 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.130 inches

**Actuator Free Position Height:**

0.080 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Switch Release Force:**

1.3 ounces

**Switch Actuating Force:**

1.4 ounces

**Actuator Movement:**

0.050 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac

**Special Features:**

The switch switches one circuit from "off" to "on" or "on" to "off" (spdt) and spring back (momentary). Switch is rated 5 amps at 250 vac and has three solder lug terminals. voltage is 250 vac/30 vdc. Housing is plastic and is 0.36 inch ht. X 0.78 inch wd. X 0.25 inch dp. They have two 0.09 inch dia. Mounting holes spaced 0.38 inch center to center (hardware not included). UI recognized, csa certified, and ce approved.

**Terminal Type And Quantity:**

3 binding post

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0