NSN 5930-01-585-0688

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-585-0688

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Overall Length:

2.937 inches

Overall Diameter:

1.162 inches

Individual Section Quantity:

4

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section front

Throw Quantity:

2 each section front

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.00 amperes resistive load ac at sea level and 0.25 amperes inductive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

NSN 5930-01-585-0688

Rotary Switch - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

