NSN 5930-01-595-7510

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-595-7510

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Overall Length:

2.245 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

Between 1.152 inches and 1.172 inches

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

End Application:

Wsd: nuclear power plants

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load ac at sea level

Special Features:

90 degrees angle of throw, two decks, one pole per deck, two positions per pole, non-shorting

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-01-595-7510

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0