

View Online at <https://aerobasegroup.com/nsn/5930-01-596-8389>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

Between 0.435 inches and 0.439 inches

**Body Length:**

Between 0.720 inches and 0.780 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.190 inches

**Actuator Height:**

0.085 inches

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Printed circuit

**Nonpile-up Contact Arrangement:**

2 two circuit, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes resistive dc

**Special Features:**

Temperature characteristics is -55 to +85 c; vibration grade 2 (10 hz to 2, 000 hz); weight is 0.30 pounds ; dielectric withstanding voltage is 1, 050 v rms; strength of actuator is 10 pounds; terminal strength is 5 pounds all directions; mechanical endurance is 100, 000 cycles and electrical endurance is 50, 000 cycles

**Test Data Document:**

Mil-prf-8805 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

4 solder stud

**Specification Data:**

81349/mil-prf-8805/110d government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0

**Mil-std (military Standard):**

Mil-prf-8805 spec.