

View Online at <https://aerobasegroup.com/nsn/5930-01-596-8389>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

Between 0.435 inches and 0.439 inches

Body Length:

Between 0.720 inches and 0.780 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.190 inches

Actuator Height:

0.085 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Printed circuit

Nonpile-up Contact Arrangement:

2 two circuit, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes resistive dc

Special Features:

Temperature characteristics is -55 to +85 c; vibration grade 2 (10 hz to 2, 000 hz); weight is 0.30 pounds ; dielectric withstanding voltage is 1, 050 v rms; strength of actuator is 10 pounds; terminal strength is 5 pounds all directions; mechanical endurance is 100, 000 cycles and electrical endurance is 50, 000 cycles

Test Data Document:

Mil-prf-8805 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

4 solder stud

Specification Data:

81349/mil-prf-8805/110d government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0

Mil-std (military Standard):

Mil-prf-8805 spec.