

View Online at <https://aerobasegroup.com/nsn/5930-01-602-1235>

Thread Length:

7.0 millimeters single pressure connection

Overall Length:

37.0 millimeters

Body Length:

28.0 millimeters

Overall Diameter:

31.0 millimeters

End Application:

Mrap rg-31

Pressure Switch Type:

Absolute

Width Across Flats:

27.0 millimeters

Operating Temperature Rating:

Between -40.0 degrees celsius and 80.0 degrees celsius

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

30.0 bar

Thread Size:

12.0 millimeters single pressure connection

Thread Pitch In Millimeters:

1.5 single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

0.4 actuation point bar and 0.6 actuation point bar

Contact Voltage Rating In Volts:

6.0 dc at sea level second voltage

Pressure Connector Type:

External seat-gasket seal, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Iso m single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0