NSN 5930-01-612-2816

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-612-2816

Body Style: Hole mounted Center To Center Distance Between Mounting Facilities Parallel To Length: Between 22.1 millimeters and 22.3 millimeters **Body Length:** Between 24.0 millimeters and 24.8 millimeters **Body Width:** Between 9.9 millimeters and 10.7 millimeters **Body Height:** Between 27.4 millimeters and 28.2 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 10.2 millimeters and 10.4 millimeters Actuator Length: 27.5 millimeters **Actuator Style:** Leaf **Actuator Width:** Between 3.9 millimeters and 4.7 millimeters **Actuator Free Position Height:** Between 3.6 millimeters and 4.4 millimeters Maximum Voltage Rating In Volts: 250.0 ac **End Application:** Drill press module **Inclosure Type:** Uninclosed **Mounting Method:** Panel and screw Switch Release Force: 16.0 ampere-turns Switch Actuating Force: 16.0 ampere-turns **Actuator Movement:** Between 2.4 differential millimeters and 6.0 differential millimeters Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes inductive ac **Terminal Type And Quantity:** 1 quick disconnect, female Shelf Life: N/a Unit Of Measure: ---

NSN 5930-01-612-2816

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

