NSN 5930-01-612-2816

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-612-2816

To Length:

To Height:

view Offiline at https://aerobasegroup.com/nsi//3930-01-012-2010
Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel
Between 22.1 millimeters and 22.3 millimeters
Body Length:
Between 24.0 millimeters and 24.8 millimeters
Body Width:
Between 9.9 millimeters and 10.7 millimeters
Body Height:
Between 27.4 millimeters and 28.2 millimeters
Center To Center Distance Between Mounting Facilities Parallel
Between 10.2 millimeters and 10.4 millimeters
Actuator Length:
27.5 millimeters
Actuator Style:
Leaf
Actuator Width:
Between 3.9 millimeters and 4.7 millimeters
Actuator Free Position Height:
Between 3.6 millimeters and 4.4 millimeters
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
Drill press module
Inclosure Type:
Uninclosed
Mounting Method:
Panel and screw
Switch Release Force:
16.0 ampere-turns
Switch Actuating Force:
16.0 ampere-turns
Actuator Movement:
Between 2.4 differential millimeters and 6.0 differential millimeters
Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes inductive ac
Terminal Type And Quantity:
1 quick disconnect, female
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-01-612-2816

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0