

View Online at <https://aerobasegroup.com/nsn/5930-01-612-2817>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 22.1 millimeters and 22.3 millimeters

Body Length:

Between 24.0 millimeters and 24.8 millimeters

Body Width:

Between 9.9 millimeters and 10.7 millimeters

Body Height:

Between 27.4 millimeters and 28.2 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 10.2 millimeters and 10.4 millimeters

Actuator Length:

Between 3.8 millimeters and 4.6 millimeters

Actuator Style:

Rectangular

Actuator Height:

Between 0.8 millimeters and 1.6 millimeters

Actuator Width:

Between 2.4 millimeters and 3.2 millimeters

Actuator Free Position Height:

Between 0.8 millimeters and 1.6 millimeters

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Uninclosed

Mounting Method:

Panel and screw

Switch Release Force:

16.0 ampere-turns

Switch Actuating Force:

16.0 ampere-turns

Actuator Movement:

Between 2.4 differential millimeters and 3.2 differential millimeters

Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes inductive ac

Terminal Type And Quantity:

1 quick disconnect, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0