

View Online at <https://aerobasegroup.com/nsn/5930-01-612-2817>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 22.1 millimeters and 22.3 millimeters

**Body Length:**

Between 24.0 millimeters and 24.8 millimeters

**Body Width:**

Between 9.9 millimeters and 10.7 millimeters

**Body Height:**

Between 27.4 millimeters and 28.2 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 10.2 millimeters and 10.4 millimeters

**Actuator Length:**

Between 3.8 millimeters and 4.6 millimeters

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.8 millimeters and 1.6 millimeters

**Actuator Width:**

Between 2.4 millimeters and 3.2 millimeters

**Actuator Free Position Height:**

Between 0.8 millimeters and 1.6 millimeters

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Panel and screw

**Switch Release Force:**

16.0 ampere-turns

**Switch Actuating Force:**

16.0 ampere-turns

**Actuator Movement:**

Between 2.4 differential millimeters and 3.2 differential millimeters

**Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes inductive ac

**Terminal Type And Quantity:**

1 quick disconnect, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0