## NSN 5930-01-614-6025

Lock Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-614-6025

Thread Class: 2a Body Style: Bushing mounted Body Diameter: 0.900 inches Body Length: 2.877 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing w/panel seal Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	
Body Style:Bushing mountedBody Diameter:0.900 inchesBody Length:2.877 inchesBuclosure Type:Yully enclosedMounting Method:Threaded bushing w/panel sealThready Qty Per Inch (tpi):24Thread Size:0.750 inchesContact Load Current Rating At Maximum Rated Voltage:2.877 milliamperes resistive dcThread Series Designator:Uns2.916 Life:N/aDenilitarization:NoFig:	Thread Class:
Bushing mounted Body Diameter: O.900 inches Body Length: 2.877 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: O.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2a
Body Diameter: 0.900 inches Body Length: 2.877 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Body Style:
0.900 inches Body Length: 2.877 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Bushing mounted
Body Length: 2.877 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Body Diameter:
2.877 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	0.900 inches
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Body Length:
Fully enclosed Mounting Method: Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: 2.877 mi	2.877 inches
Mounting Method: Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Inclosure Type:
Threaded bushing w/panel seal Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Fully enclosed
Thready Qty Per Inch (tpi): 24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Mounting Method:
24 Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Threaded bushing w/panel seal
Thread Size: 0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Thready Qty Per Inch (tpi):
0.750 inches Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	24
Contact Load Current Rating At Maximum Rated Voltage: 2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Thread Size:
2.877 milliamperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	0.750 inches
Thread Series Designator: Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Contact Load Current Rating At Maximum Rated Voltage:
Uns Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	2.877 milliamperes resistive dc
Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Thread Series Designator:
2 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Uns
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure:  Demilitarization: No Fiig:	2 threaded stud
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
1050-0	Fiig:
AU53aU	A053a0