

View Online at <https://aerobasegroup.com/nsn/5930-01-614-9639>

Thread Class:

2

Body Style:

Bushing mount

Overall Height:

2.52 inches

Bushing Length:

0.47 inches

Body Length:

1.31 inches

Body Width:

0.132 inches

Body Height:

1.35 inches

Center To Center Distance Between Terminals:

0.38 inches

Switch Actuator Quantity:

1

Actuator Style:

Rectangular

Actuator Height:

0.70 inches

Actuator Width:

0.40 inches

Actuator Position-action Relationship:

Center position maintained and down position maintained and up position maintained

Actuator Position-locking Relationship:

Center position no locking action and down position no locking action and up position no locking action

Actuator Color:

Blue single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

End Application:

Kc-135 blk 45

Mounting Surface To Terminal End Distance:

Between 1.10 inches and 1.35 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Product Name:

Switch, toggle

Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes resistive ac and 15.0 amperes inductive ac and 4.0 amperes lamp ac

Special Features:

Current ratings - 20adc res, 15adc ind, 7adclamp, 4aac lamp

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0