

View Online at <https://aerobasegroup.com/nsn/5930-01-614-9639>

**Thread Class:**

2

**Body Style:**

Bushing mount

**Overall Height:**

2.52 inches

**Bushing Length:**

0.47 inches

**Body Length:**

1.31 inches

**Body Width:**

0.132 inches

**Body Height:**

1.35 inches

**Center To Center Distance Between Terminals:**

0.38 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Rectangular

**Actuator Height:**

0.70 inches

**Actuator Width:**

0.40 inches

**Actuator Position-action Relationship:**

Center position maintained and down position maintained and up position maintained

**Actuator Position-locking Relationship:**

Center position no locking action and down position no locking action and up position no locking action

**Actuator Color:**

Blue single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**End Application:**

Kc-135 blk 45

**Mounting Surface To Terminal End Distance:**

Between 1.10 inches and 1.35 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.468 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Product Name:**

Switch, toggle

**Contact Load Current Rating At Maximum Rated Voltage:**

15.0 amperes resistive ac and 15.0 amperes inductive ac and 4.0 amperes lamp ac

**Special Features:**

Current ratings - 20adc res, 15adc ind, 7adclamp, 4aac lamp

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0