## NSN 5930-01-616-3003

Sensitive Switch - Page 1 of 1

**Demilitarization:** 

No Fiig: A053a0



View Online at https://aerobasegroup.com/nsn/5930-01-616-3003 **Body Style:** Hole mounted **Case Material:** Metal **Housing Height:** 41.5 millimeters **Housing Length:** 94.1 millimeters **Housing Width:** Between 39.3 millimeters and 40.7 millimeters Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 68.7 millimeters Center To Center Distance Between Housing Mounting Facilities Parallel To Width: Between 30.0 millimeters and 30.4 millimeters **Maximum Voltage Rating In Volts:** 250.0 ac or 125.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Screw **Switch Release Force:** 2.22 newtons **Switch Actuating Force:** 13.3 newtons **Contact Load Current Rating At Maximum Rated Voltage:** 10.0 amperes resistive ac and 0.8 amperes resistive dc **Special Features:** Supply volatage 480 ac or 250 dc; pretravel - 10 to 20 degrees; overtravel - 30 degrees; differential travel - 12 degree; actuator - side mounter roller airm; circuitry spdt-db; operating temperature - minus 10degrees c to plus 80 degrees c Shelf Life: N/a **Unit Of Measure:**