

View Online at <https://aerobasegroup.com/nsn/5930-01-616-3003>

**Body Style:**

Hole mounted

**Case Material:**

Metal

**Housing Height:**

41.5 millimeters

**Housing Length:**

94.1 millimeters

**Housing Width:**

Between 39.3 millimeters and 40.7 millimeters

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

68.7 millimeters

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

Between 30.0 millimeters and 30.4 millimeters

**Maximum Voltage Rating In Volts:**

250.0 ac or 125.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Screw

**Switch Release Force:**

2.22 newtons

**Switch Actuating Force:**

13.3 newtons

**Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes resistive ac and 0.8 amperes resistive dc

**Special Features:**

Supply volatage 480 ac or 250 dc; pretravel - 10 to 20 degrees; overtravel - 30 degrees ; differential travel - 12 degree ; actuator - side mounter roller air; circuitry spdt-db; operating temperature - minus 10degrees c to plus 80 degrees c

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0