

View Online at <https://aerobasegroup.com/nsn/5930-01-616-3003>

Body Style:

Hole mounted

Case Material:

Metal

Housing Height:

41.5 millimeters

Housing Length:

94.1 millimeters

Housing Width:

Between 39.3 millimeters and 40.7 millimeters

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

68.7 millimeters

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Between 30.0 millimeters and 30.4 millimeters

Maximum Voltage Rating In Volts:

250.0 ac or 125.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Screw

Switch Release Force:

2.22 newtons

Switch Actuating Force:

13.3 newtons

Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes resistive ac and 0.8 amperes resistive dc

Special Features:

Supply volatage 480 ac or 250 dc; pretravel - 10 to 20 degrees; overtravel - 30 degrees ; differential travel - 12 degree ; actuator - side mounter roller air; circuitry spdt-db; operating temperature - minus 10degrees c to plus 80 degrees c

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0