

View Online at <https://aerobasegroup.com/nsn/5930-01-625-1926>

**Thread Class:**

3b all pressure connection

**Thread Direction:**

Right-hand all pressure connection

**Overall Length:**

4.00 inches

**Body Length:**

Between 1.30 inches and 1.50 inches

**Overall Diameter:**

Between 4.97 inches and 5.03 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Input port

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

30.0 inches of water

**Thread Size:**

0.4375 inches all pressure connection

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, both positions maintained

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

1.0 amperes inductive load and 0.25 amperes lamp load single voltage

**Contact Stimulus Rating:**

13.0 actuation point inches of water and 10.5 deactuation point inches of water

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Product Name:**

Switch, pressure

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A048b0