

View Online at <https://aerobasegroup.com/nsn/5930-01-625-1926>

Thread Class:

3b all pressure connection

Thread Direction:

Right-hand all pressure connection

Overall Length:

4.00 inches

Body Length:

Between 1.30 inches and 1.50 inches

Overall Diameter:

Between 4.97 inches and 5.03 inches

Pressure Switch Type:

Differential

Mounting Method:

Input port

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

30.0 inches of water

Thread Size:

0.4375 inches all pressure connection

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes inductive load and 0.25 amperes lamp load single voltage

Contact Stimulus Rating:

13.0 actuation point inches of water and 10.5 deactuation point inches of water

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Product Name:

Switch, pressure

Style Designator:

Cylindrical

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0