## NSN 5930-01-625-1926

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-625-1926

View Online at https://aerobasegroup.com/nsn/5930-01-625-1926
Thread Class:
3b all pressure connection
Thread Direction:
Right-hand all pressure connection
Overall Length:
4.00 inches
Body Length:
Between 1.30 inches and 1.50 inches
Overall Diameter:
Between 4.97 inches and 5.03 inches
Pressure Switch Type:
Differential
Mounting Method:
Input port
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
20 all pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
30.0 inches of water
Thread Size:
0.4375 inches all pressure connection
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, both positions maintained
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
1.0 amperes inductive load and 0.25 amperes lamp load single voltage
Contact Stimulus Rating:
13.0 actuation point inches of water and 10.5 deactuation point inches of water
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:
Plain, threaded internal single connection
Product Name:
Switch, pressure
Style Designator:
Cylindrical
Thread Series Designator:

Thread Series Designator:
Unf all pressure connection

## NSN 5930-01-625-1926

Pressure Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0