## NSN 5930-01-625-2268

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-625-2268

**Thread Class:** 2a single mounting facility **Thread Length:** 0.375 inches single mounting facility **Overall Length:** 3.113 inches **Overall Diameter:** 1.719 inches **Individual Section Quantity: End Application:** C5m amp se **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 6 single section rear **Mounting Method:** Threaded bushing single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 60.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 2.25 amperes resistive load dc at sea level **Style Designator:** Circular, cam actuated

**Thread Series Designator:** 

Unef single mounting facility

## NSN 5930-01-625-2268

Rotary Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0