

View Online at <https://aerobasegroup.com/nsn/5930-01-632-8898>

**Body Style:**

Panel mount

**Overall Length:**

0.720 inches

**Body Diameter:**

0.469 inches

**Body Length:**

0.629 inches

**Overall Diameter:**

0.690 inches

**Unthreaded Mounting Hole Diameter:**

0.500 inches

**Switch Actuator Quantity:**

2

**Actuator Style:**

Round, flush

**Actuator Diameter:**

0.690 inches

**Actuator Height:**

0.270 inches

**Actuator Color:**

Red single actuator

**Housing Diameter:**

0.690 inches

**Maximum Voltage Rating In Volts:**

115.0 ac

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Mounting hardware

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, double break, momentary action single switch unit

**Product Name:**

Sealed dome pushbutton switch for wet and dusty zones

**Contact Load Current Rating At Maximum Rated Voltage:**

4.0 amperes inductive ac

**Special Features:**

Item includes 0.469-32 unrs-2a threaded body for mounting into panels with lockwasher and nut; case/bezel is black in color with red button; operating temp range is -55 degrees c to 85 degrees c

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

1 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0