

View Online at <https://aerobasegroup.com/nsn/5930-01-641-4070>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.844 inches

Overall Height:

0.875 inches

Body Diameter:

0.562 inches

Bushing Length:

0.750 inches

Body Length:

0.422 inches

Overall Diameter:

0.875 inches

Case Material:

Metal

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.875 inches

Actuator Height:

0.281 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal and mounting hardware

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Product Name:

Switch, snap - moistureproof

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0