

View Online at <https://aerobasegroup.com/nsn/5930-01-641-4070>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.844 inches

**Overall Height:**

0.875 inches

**Body Diameter:**

0.562 inches

**Bushing Length:**

0.750 inches

**Body Length:**

0.422 inches

**Overall Diameter:**

0.875 inches

**Case Material:**

Metal

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.875 inches

**Actuator Height:**

0.281 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal and mounting hardware

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Product Name:**

Switch, snap - moistureproof

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0