NSN 5930-01-641-4070

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Thread Class:

Body Style:

Bushing mounted

Moisture proof

Overall Length:

2a



View Online at https://aerobasegroup.com/nsn/5930-01-641-4070

| 1.844 inches | |
|-------------------------------------|--|
| Overall Height: | |
| 0.875 inches | |
| Body Diameter: | |
| 0.562 inches | |
| Bushing Length: | |
| 0.750 inches | |
| Body Length: | |
| 0.422 inches | |
| Overall Diameter: | |
| 0.875 inches | |
| Case Material: | |
| Metal | |
| Switch Actuator Quantity: | |
| 1 | |
| Actuator Style: | |
| Round | |
| Actuator Diameter: | |
| 0.875 inches | |
| Actuator Height: | |
| 0.281 inches | |
| Actuator Color: | |
| Black single actuator | |
| Illuminated Actuator Color: | |
| White single actuator | |
| Maximum Voltage Rating In Volts: | |
| 120.0 ac and 28.0 dc | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Threaded bushing | |
| Features Provided: | |
| Actuator seal and mounting hardware | |
| Thready Qty Per Inch (tpi): | |
| 24 | |

NSN 5930-01-641-4070

Push Switch - Page 2 of 2

A053a0



| Thread Size: |
|---|
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, double make, momentary action single switch unit |
| Product Name: |
| Switch, snap - moistureproof |
| Contact Load Current Rating At Maximum Rated Voltage: |
| $10.000 \ amperes \ resistive \ dc \ and \ 5.000 \ amperes \ lamp \ dc \ and \ 15.000 \ amperes \ resistive \ ac$ |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |