

View Online at <https://aerobasegroup.com/nsn/5930-01-656-9819>

**Thread Length:**

0.437 inches single mounting facility

**Overall Length:**

3.283 inches

**Overall Diameter:**

Between 1.0 inches and 1.3 inches

**Individual Section Quantity:**

5

**Operating Temperature Range:**

-65.0 to 125.0 degrees celsius

**End Application:**

Hx navy

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

9 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

9 single actuator

**Terminal Type:**

Tab, solder lug

**Detent Rotational Torque Range:**

+1.0 to 4.5 inch-pounds single actuator

**Contact Load Current Rating:**

75.0 milliamperes resistive load ac at altitude

**Product Name:**

Rotary switch

**Style Designator:**

Tap, circular, bushing mount

**Test Data Document:**

81349-mil-s-3786/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-s-3786/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0