NSN 5930-01-657-0666

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-657-0666

| Body Style: |
|--|
| Hole mounted |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.980 inches |
| |
| Body Length: |
| 1.570 inches |
| Body Width: |
| 0.630 inches |
| Body Height: |
| 2.120 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.200 inches |
| Switch Actuator Quantity: |
| 1 |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.390 inches |
| Actuator Height: |
| 0.189 inches |
| Actuator Free Position Height: |
| 0.690 inches |
| Maximum Voltage Rating In Volts: |
| 240.0 ac and 28.0 dc |
| End Application: |
| 5840-01-603-2838 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Switch Release Force: |
| 2.75 inch-ounces |
| Switch Actuating Force: |
| 2.75 inch-ounces |
| Actuator Movement: |
| 0.071 differential inches and 0.118 overtravel inches and 0.071 pretravel inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 amperes resistive ac and 5.0 amperes resistive dc |
| Precious Material And Location: |
| Contact surface silver |
| Terminal Type And Quantity: |
| 4 wire lead |
| |

NSN 5930-01-657-0666

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

