NSN 5935-00-001-2912

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-001-2912

| Thread Class: |
|---|
| 2a and 2b |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.906 inches |
| Overall Diameter: |
| 0.625 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 2 |
| Contact Removability: |
| Nonremovable all mating ends all contact groupings |
| Contact Maximum Ac Voltage Rating In Volts: |
| 1000.0 all mating ends all contact groupings |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell and internally threaded coupling ring |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 all mating ends all contact groupings |
| Thready Qty Per Inch (tpi): |
| 24 and 28 |
| Thread Size: |
| 0.625 inches and 0.438 inches |
| Contact Material: |
| Copper alloy all mating ends all contact groupings |
| Contact Surface Treatment: |
| Gold all mating ends all contact groupings |
| Shell Material: |
| Stainless steel |
| Included Contact Quantity: |
| 1 2nd mating end all contact groupings |
| Included Contact Type: |
| Coaxial socket 2nd mating end all contact groupings |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |

0.010 gold grains, troy

NSN 5935-00-001-2912

Connector Adapter - Page 2 of 2



| Precious | Material: |
|----------|-----------|
| Gold | |

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0