## NSN 5935-00-001-3139

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-001-3139

**Body Style:** Straight shape, internal coupling Overall Length: 0.875 inches Overall Diameter: 0.375 inches **Cable Entrance Diameter:** Between 0.078 inches and 0.090 inches **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Compression nut **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Copper alloy

**Shell Surface Treatment:** 

Gold and silver

**Shell Surface Treatment Specification:** 

Qq-s-365 federal specification 2nd treatment response and mil-g-45204 military specification 1st treatment response

**Shell Material Specification:** 

Qq-b-626, comp 22 1/2 hard federal specification single material response

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-00-001-3139

Electrical Plug Connector - Page 2 of 2



Praci	ioue	Mataria	I And I	Location
rieu	IUU3	ıvıatel la	ı Allu	LUCALIUII.

Contact and body surface gold and contact and body surface silver

**Precious Material And Weight:** 

0.105 gold grains, troy and 0.105 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.