Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-001-3158

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| Between 1.406 inches and 1.471 inches |
| Overall Height: |
| Between 0.929 inches and 0.945 inches |
| Overall Width: |
| Between 0.929 inches and 0.945 inches |
| Environmental Protection: |
| Moisture resistant and salt water resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| Between 0.116 inches and 0.126 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| Between 0.714 inches and 0.724 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 0.714 inches and 0.724 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.894 inches and 0.906 inches |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 10-12 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.625 inches |
| |

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location: | |
|---|--|
| Back single mating end single contact grouping | |
| Contact Material: | |
| Copper alloy single mating end single contact grouping | |
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping | |
| Contact Surface Treatment Specification: | |
| Mil-g-45204, type 1, class 1 military specification single treatment response single mating | g end single contact grouping |
| Terminal Type: | |
| Crimp single mating end single contact grouping | |
| Shell Material: | |
| Aluminum | |
| Shell Surface Treatment: | |
| Cadmium | |
| Shell Surface Treatment Specification: | |
| Qq-p-416, type 2, cl 3 federal specification single treatment response | |
| Shell Material Specification: | |
| Qq-a-367, comp 6061, temper t6 federal specification single material response | |
| Included Contact Quantity: | |
| 12 single mating end single contact grouping | |
| Included Contact Type: | |
| Round socket single mating end single contact grouping | |
| Precious Material And Location: | |
| Contact surfaces gold | |
| Precious Material And Weight: | |
| 0.012 gold grains, troy | |
| Precious Material: | |
| Gold | |
| Test Data Document: | |
| 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., th | nat reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publication | |
| environmental and performance requirements and test conditions that are shown as "typi | |
| Thread Series Designator: | |
| Un | |
| Specification Data: | |
| 81349-mil-c-81511/21 government specification | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (military Standard): | |
| • | |