Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-001-5728

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.931 inches
Overall Height:
1.219 inches
Overall Width:
1.219 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
0.447 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
16-42 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
400.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
550.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
82.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Length:
0.219 inches

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.937 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic silicone single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and nickel **Included Contact Quantity:** 42 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.042 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.