Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-003-5825

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, flange mount
Overall Length:
0.462 inches
Bushing Diameter:
0.325 inches
Overall Height:
0.620 inches
Environmental Protection:
Heat resistant and moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.078 inches
Distance Between Mounting Facility Centers:
0.346 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
7p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
24
Thread Size:
0.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Insert Material: Plastic epoxy single mating end **Terminal Type:** Wire loop single mating end single contact grouping **Shell Material:** Plastic **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.007 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0