

View Online at <https://aerobasegroup.com/nsn/5935-00-003-9822>

**Environmental Protection:**

Thermal shock resistant and vibration resistant and shock resistant and corrosion resistant and moisture resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

16-61 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

30.0 and 120.0 and 210.0 and 285.0

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Glass single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Tin

**Shell Surface Treatment Specification:**

Mil-t-10727 military specification single treatment response

**Shell Material Specification:**

Qq-s-637 federal specification single material response

**Included Contact Quantity:**

61 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round pin single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.