Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-004-0129

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 1.570 inches and 1.580 inches

Overall Height:

0.702 inches

Overall Width:

Between 0.325 inches and 0.335 inches

Unthreaded Mounting Hole Diameter:

0.116 inches

Distance Between Mounting Facility Centers:

1.275 inches

Board Accommodated Length:

0.895 inches single board and 0.905 inches single board

Board Accommodated Width:

0.300 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Switching contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Fixed contact to contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

NSN 5935-00-004-0129

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Bifurcated spring single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.020 gold grains, troy and 0.020 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.