## NSN 5935-00-004-5877

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5035-00-004-5877

View Online at https://aerobasegroup.com/nsn/5935-00-004-5877
Body Style:
Straight shape threaded
Overall Length:
Between 0.563 inches and 0.593 inches
Overall Diameter:
Between 0.735 inches and 0.765 inches
Environmental Protection:
Hermetic
Mating End Quantity:
1
Contact Position Arrangement Style:
7p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping  Shell Material:
Aluminum alloy Shell Surface Treatment:
Tin
Included Contact Quantity:
monucu comact quantity.

7 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-00-004-5877

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Solder flange mtd
<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.